



AGAT POS LED TUNABLE WHITE

Tunable White luminaires










Luminary body made from steel sheet powder coated in white. Luminary adapted to be mounted in 600x600 module ceilings and with adaptive frame in plasterboard ceilings. It is equipped with highly efficient LED sources of the newest lighting generation, with the average durability of 60000 h. Diffuser is made from polymethyl methacrylate with micro prism structure (micro prism part of diffuser is the outer side of the luminary). Luminary resistant to solids, dust, and liquids penetration (IP20). LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.



Printing house "Print Group", Szczecin


















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
AGAT POS LED 4400 TUNABLE WHITE	4304÷4574 (2700÷6500 K)	30÷32 (6500÷2700 K)	2700 ÷ 6500	596 x 596 x 55
AGAT POS LED 6600 TUNABLE WHITE	6456÷6861 (2700÷6500 K)	45÷48 (6500÷2700 K)	2700 ÷ 6500	596 x 596 x 55

Technical drawing:



Light and electrical features:

Light source	LED	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	50000	
Lx/By	L80/B10	
CRI	>80	
SDCM (LED sources)	3	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor $\cos \phi$	>0,95	

Mechanical features:

Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)

Additional information:

The luminaire can be made in CLO version.