



ARTSHAPE SIX LED

Architectural luminaires



Modernistic architectural luminaire in shapes of popular geometrical figures and fashionable design of simple form. The luminaire is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palette, the luminaires allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminaire is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.




Jagiellonia Białystok - training center



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ARTSHAPE SIX LED SMALL EDGE 3000	2970	25	4000	650 x 592 x 85
ARTSHAPE SIX LED SMALL EDGE 6000	5681	50	3000	650 x 592 x 85
ARTSHAPE SIX LED SMALL EDGE 9000	8910	70	4000	650 x 592 x 85
ARTSHAPE SIX LED MEDIUM EDGE 4500	4455	35	4000	900 x 809 x 85
ARTSHAPE SIX LED MEDIUM EDGE 9000	8910	70	4000	900 x 809 x 85
ARTSHAPE SIX LED LARGE EDGE 6000	5940	50	4000	1170 x 1043 x 85
ARTSHAPE SIX LED LARGE EDGE 12000	11880	92	4000	1170 x 1043 x 85
ARTSHAPE SIX LED SMALL EDGE TW 4000	4200	40	2700 ÷ 6500	650 x 592 x 85
ARTSHAPE SIX LED MEDIUM EDGE TW 6000	5880	57	2700 ÷ 6500	900 x 809 x 85
ARTSHAPE SIX LED LARGE EDGE TW 8000	8040	77	2700 ÷ 6500	1170 x 1043 x 85
ARTSHAPE SIX LED SMALL EDGE UP&DOWN 2800/6000	2888/5940	75	4000	650 x 592 x 85
ARTSHAPE SIX LED MEDIUM EDGE UP&DOWN 4000/9000	4104/8910	105	4000	900 x 809 x 85
ARTSHAPE SIX LED LARGE EDGE UP&DOWN 5200/12000	5320/11880	138	4000	1170 x 1043 x 85
ARTSHAPE SIX LED SMALL FULL UP&DOWN 2800/5500	2888/5445	68	4000	650 x 592 x 85
ARTSHAPE SIX LED MEDIUM FULL UP&DOWN 4000/12000	4104/12874	135	4000	900 x 809 x 85
ARTSHAPE SIX LED LARGE FULL UP&DOWN 5000/21000	5320/21782	218	4000	1170 x 1043 x 85

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000/35000
Lx/By	L80/B10
CRI	>80
SDCM (LED sources)	3/4
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	0 ÷ 30
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos ϕ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)

Additional information:


On individual request it is possible to make EDGE luminaires in larger sizes and in RGBW versions. These luminaires are characterised by tightly closed chamber of LED light sources (IP65) thanks to this impurities are not visible on the diffuser for a long time of exploitation. Temperature range for storage and transport from 0° C to 40° C. The luminaire can be made in CLO version.

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 07-05-2025

Dodatkowe informacje / Additional information / Zusätzliche Informationen:

Artshape EDGE

Artshape FULL




Artshape Up & Down (Round / Three / SQ / Six / Line)



Artshape TW (Tunable white)
(Round / Three / Sq / Six / Line)

Artshape RGB
(Round Edge / Three Edge / Sq Edge / Six Edge)



2700 ÷ 6500 K