



ATENA LED PRO

Industrial luminaires





Atena LED Pro is a solution for industrial spaces, combining efficiency of over 200 lm/W, durability, and adaptability. Its aerodynamic design enables passive cooling, while flexible mounting options and accessories like anti-glare systems and motion sensors enhance its versatility. Built to perform in tough conditions with temperatures from -40°C to +40°C, Atena LED Pro is reliable, efficient, and tailored for excellence.



















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
ATENA LED PRO 20000 OPTICS-120	20567,7	100	4000	Ø260 x 108
ATENA LED PRO 20000 OPTICS-60	20567,7	100	4000	Ø260 x 108
ATENA LED PRO 20000 OPTICS-90	20567,7	100	4000	Ø260 x 108
ATENA LED PRO 30000 OPTICS-120	30641,3	147,5	4000	Ø300 x 111
ATENA LED PRO 30000 OPTICS-60	30641,3	147,5	4000	Ø300 x 111
ATENA LED PRO 30000 OPTICS-90	30641,3	147,5	4000	Ø300 x 111
ATENA LED PRO 40000 OPTICS-120	40196,7	196	4000	Ø350 x 112
ATENA LED PRO 40000 OPTICS-60	40196,7	196	4000	Ø350 x 112
ATENA LED PRO 40000 OPTICS-90	40196,7	196	4000	Ø350 x 112

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	-40 ÷ 40
Driver	standard on/off (E) DIM DALI (EDD) *

^{*} Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9005 (black)
Diffuser	optical system based on PC lenses