




## BERYL NEW LED K/L4

### Recessed luminaires



Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Beryl New LED K has higher efficiency and efficiency than the previous version. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions. The luminaire has the ability to adjust the optics in two planes (in the vertical axis by 359° and to the left and right 15°). Note: the color of the frame and housing has a slightly different shade than the color of the inner reflector cover.






## Main parameters:

| Name                      | Luminous flux LED [lm] | Power of luminaire [W] | Color [K]   | Dimensions A x B x H [mm] |
|---------------------------|------------------------|------------------------|-------------|---------------------------|
| BERYL NEW LED K-1/L4 1800 | 8000 / 8232            | 51,2                   | 3000 / 4000 | 472 x 119 x 99            |
| BERYL NEW LED K-2/L4 3600 | 16716 / 17220          | 102                    | 3000 / 4000 | 650 x 164 x 137           |

## Technical drawing:



## Light and electrical features:

|                                  |   |
|----------------------------------|---|
| Light source                     | LED   |
| Voltage                          | 220..240 V, 50..60 Hz   |
| Lifetime of LED sources [h]      | 83000 (1) / 100000 (2) / 100000 (3) / 86000 (1) / 100000 (2) / 100000 (3) |
| Lx/By                            | L90/B10 (1) / L80/B10 (2) / L70/B10 (3)                                   |
| CRI                              | 85/80   |
| SDCM (LED sources)               | 2   |
| Operating temperature range [°C] | 5 ÷ 30  |
| Driver                           | standard on/off (E)<br>DIM DALI (EDD) *                                   |
| Power factor cos φ               | >0,95   |

\* Variant to specify when ordering

## Mechanical features:

|          |   |
|----------|---|
| Assembly | mounted in module ceilings, as well as plasterboard ceilings  |
| Material | aluminum  |
| Color    | RAL 9005 (black)<br>RAL 9010 (white) *  |
| Diffuser | transparent PMMA<br>Micro-PRM (micro-prismatic diffuser PMMA)<br>PLX (PMMA opal)<br>transparent glass |

## Additional information:

The luminaire can be made in CLO version.