



## BONANOVA

Industrial luminaires




Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.



## Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
BONANOVA 12000 MEDIUM	12432 / 12864	71	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 12000 WIDE	12432 / 12864	71	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 12000 ULTRA-WIDE	12432 / 12864	71	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 16000 MEDIUM	17016 / 17688	101,5	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 16000 WIDE	17016 / 17688	101,5	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 16000 ULTRA-WIDE	17016 / 17688	101,5	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 20000 MEDIUM	21332 / 22296	133,3	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 20000 WIDE	21332 / 22296	133,3	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 20000 ULTRA-WIDE	21332 / 22296	133,3	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 24000 MEDIUM	24380 / 25588	157,8	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 24000 WIDE	24380 / 25588	157,8	3000 / 4000 / 5700	Ø480 x 177
BONANOVA 24000 ULTRA-WIDE	24380 / 25588	157,8	3000 / 4000 / 5700	Ø480 x 177

## Technical drawing:



**Light and electrical features:**

<b>Light source</b>	LED
<b>Voltage</b>	220..240 V, 50..60 Hz
<b>Lifetime of LED sources [h]</b>	100000
<b>Lx/By</b>	L80/B10
<b>CRI</b>	>80
<b>SDCM (LED sources)</b>	3
<b>Operating temperature range [°C]</b>	-40 ÷ 35
<b>Driver</b>	standard on/off (E) DIM DALI (EDD) *
<b>Power factor cos φ</b>	>0,95

\* Variant to specify when ordering

**Mechanical features:**

<b>Assembly</b>	surface mounted on slings
<b>Material</b>	aluminum
<b>Color</b>	RAL 9007 (dark grey)
<b>Diffuser</b>	hardened transparent glass



Note: The power shown refers to the whole system (tolerance +/- 10%).  
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).  
Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 17-04-2026