



KUBIK CEILING ECO LED

Outdoor luminaires









Architectural luminaire designed for ceiling mounting. The body is made of aluminum. Interchangeable light sources with the popular GU10 socket. The ergonomic shapes of the luminaire allow the use of KUBIK in almost every building. Very easy assembly. Luminaire with IP54 protection rating.



Nova Królikarnia, Warsaw













Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
KUBIK CEILING ECO LED 1X GU10	depending on source	depending on source	depending on source	120 x 120 x 120
KUBIK CEILING ECO LED 2X GU10	depending on source	depending on source	depending on source	200 x 120 x 120

Technical drawing:



Light and electrical features:

Light source	RETROFIT GU10 (not included)		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	depending on source		
Lx/By	depending on source		
CRI	depending on source		
SDCM (LED sources)	depending on source		
Driver	none		

^{*} Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on ceiling		
Material	aluminum		
Color	RAL 9005 (black) RAL 9016 (white) RAL 7016 (anthracite, metallic, fine structure) *		
Diffuser	PC (opalescent polycarbonate)		