



LUXWALL DECO LED

Architectural luminaires










Architectural luminaire, wall mounted for decorative or accent lighting of representative interiors, halls or corridors. Eagerly used in such facilities as hotels, palaces, villas or art galleries. The body is made of steel painted white (RAL 9016). Other colors available upon special request. Luminaire reflector made of polished stainless steel (possibility of painting in white). The product is available in two variants due to the light source. It can be equipped with LED sources and an electronic driver or have a G9 base for interchangeable sources of general use that do not require a dedicated driver. In-direct luminaire.















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
LUXWALL DECO LED 1X G9	depending on source	depending on source	depending on source	260 x 103 x 220
LUXWALL DECO LED 4X1,7W	608	10	4000	260 x 103 x 220

Technical drawing:



Light and electrical features:

Light source	RETROFIT G9 (not included)/LED		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	depending on source/50000		
Lx/By	depending on source/L70/B50		
CRI	depending on source/>80		
SDCM (LED sources)	depending on source		
Operating temperature range [°C]	5 ÷ 30		
Driver	none standard on/off (E) *		
Power factor cos φ	>0,5		

^{*} Variant to specify when ordering

Mechanical features:

Assembly	mounted on wall
Material	steel sheet
Color	RAL 9016 (white) grey *
Diffuser	none