



LUXCAN PRO

Projectors




Product for different applications. Various optics, based on lenses, provide a wide range of possibilities, from the narrow beam, indirect, to the wide beam. Available with the possibility of ordering a non-standard version. Cylindrical spotlight setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for Installation on the triphasic track. Body built in extruded aluminium painted with high quality coating.



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
LUXCAN PRO 2000	2000 / 2058 / 1659 / 1706	13,9	3000 / 4000	Ø90 x 187
LUXCAN PRO 3000	3018,8 / 3108 / 2504,3 / 2577,8	19	3000 / 4000	Ø90 x 187
LUXCAN PRO 4000	4179 / 4305 / 3470,3 / 3575,3	26,7	3000 / 4000	Ø90 x 187
LUXCAN PRO 5000	5124 / 5276 / 4252 / 4378,5	35	3000 / 4000	Ø90 x 187
LUXCAN PRO L/D 2000	2000 / 2058 / 1659 / 1706	13,9	3000 / 4000	Ø90 x 187
LUXCAN PRO L/D 3000	3018,8 / 3108 / 2504,3 / 2577,8	19	3000 / 4000	Ø90 x 187
LUXCAN PRO L/D 4000	4179 / 4305 / 3470,3 / 3575,3	26,7	3000 / 4000	Ø90 x 187
LUXCAN PRO L/G 2000	2000 / 2058 / 1659 / 1706	13,9	3000 / 4000	Ø90 x 187
LUXCAN PRO L/G 3000	3018,8 / 3108 / 2504,3 / 2577,8	19	3000 / 4000	Ø90 x 187
LUXCAN PRO L/G 4000	4179 / 4305 / 3470,3 / 3575,3	26,7	3000 / 4000	Ø90 x 187
LUXCAN PRO L/T 2000	2000 / 2058 / 1659 / 1706	13,9	3000 / 4000	Ø90 x 187
LUXCAN PRO L/T 3000	3018,8 / 3108 / 2504,3 / 2577,8	19	3000 / 4000	Ø90 x 187
LUXCAN PRO L/T 4000	4179 / 4305 / 3470,3 / 3575,3	26,7	3000 / 4000	Ø90 x 187
LUXCAN PRO L/M 2000	2000 / 2058 / 1659 / 1706	13,9	3000 / 4000	Ø90 x 187
LUXCAN PRO L/M 3000	3018,8 / 3108 / 2504,3 / 2577,8	19	3000 / 4000	Ø90 x 187
LUXCAN PRO L/M 4000	4179 / 4305 / 3470,3 / 3575,3	26,7	3000 / 4000	Ø90 x 187

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	83000 (1) / 100000 (2) /86000 (1) / 100000 (2) /82000 (1) / 100000 (2)
Lx/By	L90/B10 (1) / L80/B10 (2)
CRI	>80/>90
SDCM (LED sources)	3
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	mounted on a three-phase track
Material	aluminum
Color	RAL 9003 (white)
Diffuser	transparent PMMA



Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 21-11-2024