



METEOR LED COMPACT

Compact



Surface mounted luminaires equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminary mounted directly on ceilings by raw plugs.




Environmental House of self-help, Białystok



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
METEOR LED COMPACT 4000	4280,2 / 4458,5	24,7	3000 / 4000	1255 x 207 x 71
METEOR LED COMPACT 6000	6126,6 / 6381,8	37,7	3000 / 4000	1255 x 207 x 71
METEOR LED COMPACT 8000	8560 / 8918	49,3	3000 / 4000	1255 x 207 x 71
METEOR LED COMPACT 4000 IP44	4280,2 / 4458,5	24,7	3000 / 4000	1255 x 207 x 71
METEOR LED COMPACT 6000 IP44	6126,6 / 6381,8	37,7	3000 / 4000	1255 x 207 x 71
METEOR LED COMPACT 8000 IP44	8560 / 8918	49,3	3000 / 4000	1255 x 207 x 71

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	-20 ÷ 35
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	PMMA opal

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 21-11-2024