



NUMANCIA LED

Outdoor luminaires









Technical floodlight for big spaces. Can be used as indoor or outdoor luminaire at high heights where top light distribution control is required. Ideal for outdoor industrial areas, loading bays, car parks, recreational sports facilities and outdoor open areas. Designed for wall surface mounted, with specific stirrup construction that eases installation and allows tilting of 240°. Luminaire body built in die-cast aluminium with protective hardened glass and finish in RAL 9023 (dark grey). Tool-free and fast access to inner parts. Luminaire has a high environment protection of IP66 and IK09 impact resistant, is also provided with inner pressure balancing system. Luminaire adds in an PMMA lens system and multiple optical distributions. Luminaire builtin an Electronic Control Gear.















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
NUMANCIA M LED 25000	24976	150	4000	395 x 473 x 93
NUMANCIA M LED 31000	30950	199,3	4000	395 x 473 x 93
NUMANCIA S LED 15000	15223	100	4000	295 x 385 x 77

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	85000 (1) / 134000 (2)
Lx/By	L80/B10 (1) / L70/B10 (2)
CRI	>70
SDCM (LED sources)	5
Photobiological risk class (IEC/EN 62471)	RG1
Operating temperature range [°C]	-35 ÷ 35
Driver	standard on/off (E)

Mechanical features:

Assembly	mounted on wall
Material	aluminum
Color	RAL 9023 (dark grey)
Diffuser	SH (transparent hardened glass)