

Product: X-LINE PRO 2000 LOUVER EDD 04 830 / L-564MM

Index: 19.2109.3133.04



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a single version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information

Category	Surface mounted luminaires
Family	X-LINE PRO
Name	X-LINE PRO 2000 LOUVER EDD 04 830 / L-564MM
Index	19.2109.3133.04
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	2105,5
LED power [W]	11,2
Luminaire luminous flux [lm]	2044,5
Power of luminaire [W]	13,2
Luminaire's light efficiency [lm/W]	154,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
3	
Protection degree	IP40
	IP40 220240 V, 5060 Hz
Protection degree	
Protection degree Voltage	220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000
Protection degree Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 100000 L80/B10
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 100000 L80/B10 5 ÷ 35




	+-
Mechanical da	





Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Material	aluminum
Color	RAL 9005 (black)
Diffuser	LOUVER (anti-glare louver)
Impact resistant	IK04
Dimensions [mm]	564 x 60 x 70

A graph of light



Accessories

Index 6E1-500KW041P-5

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 5X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.2117.0007.04

Name X-LINE PRO COMPACT L-DOWN SURFACE BRACKET SET 04

