

**Product: X-LINE PRO 3000 LOUVER E 34 840 / L-844MM** 

Index: 19.2109.3241.34



### **Description**

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a single version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

#### **Product information**

Category	Surface mounted luminaires	
Family	X-LINE PRO	
Name	X-LINE PRO 3000 LOUVER E 34 840 / L-844MM	
Index	19.2109.3241.34	













## Light and electrical data

Light source	LED
Luminous flux LED [lm]	3324
LED power [W]	16,8
Luminaire luminous flux [lm]	3227,6
Power of luminaire [W]	19,1
Luminaire's light efficiency [lm/W]	169
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 35 (B16), 36 (C10), 59 (C16)




	+-
Mechanical da	






Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Material	aluminum
Color	RAL 9016 (white)
Diffuser	LOUVER (anti-glare louver)
Impact resistant	IK04
Weight [kg]	1,55
Dimensions [mm]	844 x 60 x 70

# A graph of light





#### **Accessories**


Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.2117.0007.34

Name X-LINE PRO COMPACT L-DOWN SURFACE BRACKET SET 34

