

## Product: X-LINE PRO 8000 LOUVER EDD 04 830 / L-2244MM Index: 19.2109.3533.04



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a single version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Category Surface mounted	luminaires
	Family X-LINE PRO	
	Name X-LINE PRO 8000	LOUVER EDD 04 830 / L-2244MM
	Index 19.2109.3533.04	
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	8424
	LED power [W]	44,8
	Luminaire luminous flux [lm]	8179,7
	Power of luminaire [W]	50,9
	Luminaire's light efficiency [lm/W	/] 160,7
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiological risk class (IEC/E 62471)	N <b>RG0</b>
	Protection against electric shock	I I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C	C] 5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)



