

## Product: X-LINE PRO 8000 LOUVER E 04 840 / L-2244MM Index: 19.2109.3541.04



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a single version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Category	Surf <mark>ace moun</mark> ted lumina	ires
	Family	X-LINE PRO	
	Name	X-LINE PRO 8000 LOUVE	R E 04 840 / L-2244MM
	Index	19.2109.3541.04	
Light and electrical data	Light source	)	LED
J	Luminous flu	ux LED [lm]	8864
	LED power	[W]	44,8
	Luminaire lu	ımin <mark>ous flux [lm]</mark>	8606,9
	Power of lur	ninaire [W]	50,9
	Luminaire's	light efficiency [lm/W]	169,1
	Color of the	light [K]	4000
	CRI		>80
	SDCM (LED	sources)	3
	Beam angle	[°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiolog 62471)	ical risk class (IEC/EN	RG0
	Protection a	gainst electric shock	1
	Protection degree		IP40
Voltage Lifetime of LED sources [h] Lx/By			220240 V, 5060 Hz
		ED sources [h]	100000
			L80/B10
	Operating te	emperature range [°C]	5 ÷ 35
	Driver Power factor cos φ		standard on/off (E)
			>0,95
	Circuit load	capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)



