

Product: X-LINE PRO 2000 LOUVER EDD 04 840 LINE / L-560MM Index: 19.2110.3143.04



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


Product information	Category Surface mounted lumi	inaires	
	Family X-LINE PRO LINE		
	Name X-LINE PRO 2000 LOU	X-LINE PRO 2000 LOUVER EDD 04 840 LINE / L-560MM	
	Index 19.2110.3143.04		
Light and electrical data	Light source	LED	
	Luminous flux LED [lm]	2216,3	
	LED power [W]	11,2	
	Luminaire luminous flux [lm]	2152	
	Power of luminaire [W]	13,2	
	Luminaire's light efficiency [lm/W]	163	
	Color of the light [K]	4000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°	
	Photobiological risk class (IEC/EN 62471)	RG0	
	Protection against electric shock	I	
	Protection degree	IP40	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LED sources [h]	100000	
	Lx/By	L80/B10	
	Operating temperature range [°C]	5 ÷ 35	
	Driver	DIM DALI (EDD)	
	Power factor $\cos \phi$	>0,95	
	Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)	




Mechanical data	⊟H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum RAL 9005 (black) LOUVER (anti-glare louver) IK04 560 x 60 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 320 45° 60° 45° 480 45° 45° 0° 15° 10° 15° 10° 15°




Accessories









Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 04





Index 19.2110.0004.04 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 04






Index 19.2110.0001.04

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.04 Name X-LINE PRO LOUVER LINE MIDDLE SET 04



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025