

Product: X-LINE PRO 3000 LOUVER EDD 34 830 LINE / L-840MM Index: 19.2110.3233.34



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


Product information	CategorySurface mounted lumFamilyX-LINE PRO LINENameX-LINE PRO 3000 LOUIndex19.2110.3233.34	inaires JVER EDD 34 830 LINE / L-840MM \textcircled{E} \textcircled{P}_{40} \swarrow \textcircled{M}_{ndoor} \overleftrightarrow{C}
Light and electrical data	Light source Luminous flux LED [lm]	LED 3159
	LED power [W]	16,8
	Luminaire luminous flux [lm]	3067,4
	Power of luminaire [W] Luminaire's light efficiency [Im/W]	19,1 160,6
		3000
	Color of the light [K] CRI	>80
		3
	SDCM (LED sources)	3 (C0-C180) / (C90-C270) - 82,4° / 76,2°
	Beam angle [°]	RG0
	Photobiological risk class (IEC/EN 62471)	RGU
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)




Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum RAL 9016 (white) LOUVER (anti-glare louver) IK04
A graph of light		Dimensions [mm]	840 x 60 x 70
			<u>30° 15° 0° 15° 30°</u> <u>cd/klm</u> η = 97%




Accessories








Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34







Index 19.2110.0004.34 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 34



Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE FRONT+END SET 34





Index 19.2110.0002.34 Name X-LINE PRO LOUVER LINE MIDDLE SET 34

