

Product: X-LINE PRO 4000 LOUVER E 34 830 LINE / L-1120MM Index: 19.2110.3331.34



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Category	Surface mounted luminai	res l
	Family	X-LINE PRO LINE	
	Name	X-LINE PRO 4000 LOUVER	R E 34 830 LINE / L-1120MM
	Index	19.2110.3331.34	
Light and electrical data	Light source	ce	LED
ů.	Luminous	flux LED [lm]	4212
	LED power	r [W]	22,4
	Luminaire	luminous flux [lm]	4089,9
	Power of lu	uminaire [W]	25,5
	Luminaire's light efficiency [lm/W]		160,4
	Color of th	e light [K]	3000
	CRI		>80
	SDCM (LED sources)		3
	Beam angle [°]		(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiological risk class (IEC/EN 62471)		RG0
	Protection against electric shock		I
	Protection degree		IP40
	Voltage		220240 V, 5060 Hz
	Lifetime of LED sources [h]		100000
	Lx/By		L80/B10
	Operating temperature range [°C]		5 ÷ 35
	Driver		standard on/off (E)
	Power factor $\cos \phi$		>0,95
	Circuit load	d capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏tH ⊌++ B	Assembly Material	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum
- A →	В	Color	RAL 9016 (white)
		Diffuser	LOUVER (anti-glare louver)
		Impact resistant	IK04
		Dimensions [mm]	1120 x 60 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 480 45° 480 45° 45° 40° 45° 45° 40° 45° 45° 480 45° 45° 45° 45° 45° 45° 45° 45° 45° 45°




Accessories







Index 19.2110.0003.34

Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34












Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.34 Name X-LINE PRO LOUVER LINE MIDDLE SET 34



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025