

## Product: X-LINE PRO 4000 LOUVER EDD 34 830 LINE / L-1120MM Index: 19.2110.3333.34



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


| Product information       | Category Surface mounted<br>Family X-LINE PRO LINE |   |
|---------------------------|--|---|
|                           |  | LOUVER EDD 34 830 LINE / L-1120MM         |
|                           | Index 19.2110.3333.34                              |   |
|                           |  |   |
| Light and electrical data | Light source                                       | LED                                       |
|                           | Luminous flux LED [lm]                             | 4212                                      |
|                           | LED power [W]                                      | 22,4                                      |
|                           | Luminaire luminous flux [lm]                       | 4089,9                                    |
|                           | Power of luminaire [W]                             | 25,5                                      |
|                           | Luminaire's light efficiency [lm/                  | W] 160,4                                  |
|                           | Color of the light [K]                             | 3000                                      |
|                           | CRI  | >80                                       |
|                           | SDCM (LED sources)                                 | 3   |
|                           | Beam angle [°]                                     | (C0-C180) / (C90-C270) - 82,4° / 76,2°    |
|                           | Photobiological risk class (IEC/<br>62471)         | EN RGO                                    |
|                           | Protection against electric show                   | sk I                                      |
|                           | Protection degree                                  | IP40                                      |
|                           | Voltage  | 220240 V, 5060 Hz                         |
|                           | Lifetime of LED sources [h]                        | 100000                                    |
|                           | Lx/By  | L80/B10                                   |
|                           | Operating temperature range [                      | °C] 5 ÷ 35                                |
|                           | Driver   | DIM DALI (EDD)                            |
|                           | Power factor $\cos \phi$                           | >0,95                                     |
|                           | Circuit load capacity                              | 17 (B10), 28 (B16), 26 (C10), 41<br>(C16) |




| Mechanical data  | □tH<br>⊌++ | Assembly<br>Material | directly mounted to ceiling construction or<br>surface mounted on slings using accessories<br>aluminum  |
|------------------|------------|----------------------|---|
| - A →            | В          | Color                | RAL 9016 (white)  |
|                  |            | Diffuser             | LOUVER (anti-glare louver)  |
|                  |            | Impact resistant     | IK04  |
|                  |            | Dimensions [mm]      | 1120 x 60 x 70  |
| A graph of light |            |                      | 105°<br>90°<br>75°<br>60°<br>45°<br>45°<br>45°<br>480<br>45°<br>480<br>45°<br>45°<br>480<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>480<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45°<br>45° |
|                  |            |                      |   |
|                  |            |                      |   |




## **Accessories**








Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34







Index 19.2110.0004.34 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 34



Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE FRONT+END SET 34





Index 19.2110.0002.34 Name X-LINE PRO LOUVER LINE MIDDLE SET 34

