

Product: X-LINE PRO 4000 LOUVER E 04 840 LINE / L-1120MM Index: 19.2110.3341.04



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Catego	ory Surface mounted	luminaires	
	Family	X-LINE PRO LINE		
	Name	X-LINE PRO 4000 I	X-LINE PRO 4000 LOUVER E 04 840 LINE / L-1120MM	
	Index	19.2110.3341.04		
Light and electrical data	Light s	source	LED	
	Lumin	ous flux LED [lm]	4432	
		ower [W]	22,4	
	Lumina	aire lumin <mark>ous flux [lm]</mark>	4303,5	
	Power	of luminaire [W]	25,5	
	Lumina	aire's light effic <mark>iency [lm/W</mark>	/] 168,8	
	Color	of the light [K]	4000	
	CRI		>80	
	SDCM	(LED sources)	3	
	Beam	angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°	
	Photok 62471	biological risk class (IEC/E)	N RG0	
	Protec	tion against electric shock		
	Protec	tion degree	IP40	
	Voltage	е	220240 V, 5060 Hz	
	Lifetim	e of LED sources [h]	100000	
	Lx/By		L80/B10	
	Opera	ting temperature range [°	C] 5 ÷ 35	
	Driver		standard on/off (E)	
	Power	factor cos φ	>0,95	
	Circuit	load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)	



Mechanical data	;н	Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Α	l⊷+l B	Material	aluminum
		Color	RAL 9005 (black)
		Diffuser	LOUVER (anti-glare louver)
		Impact resistant	IK04
		Dimensions [mm]	1120 x 60 x 70
A graph of light			105° 90° 75° 60° 45° 45° 480 480 45° 45° 45° 45° 45° 45° 45° 45°




Accessories









Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 04












Name X-LINE PRO LOUVER LINE FRONT+END SET 04







Index 19.2110.0002.04

