

## Product: X-LINE PRO 4000 LOUVER E 24 840 LINE / L-1120MM Index: 19.2110.3341.24



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Ca	ategory	Surface mounted luminai	res
	Fa	amily	X-LINE PRO LINE	
	Na	ame X-LINE PRO 4000 LOUVER E 24 840 LINE / L-1120MM		
	In	ndex	19.2110.3341.24	
Light and electrical data	Li	ight source		LED
	Lu	uminous flu	ux LED [lm]	4432
	LE	ED power	[W]	22,4
	Lu	uminaire lu	ımin <mark>ous flux [lm]</mark>	4303,5
	P	ower of lur	ninaire [W]	25,5
	Lt	uminaire's	light efficiency [lm/W]	168,8
	C	olor of the	light [K]	4000
	C	RI		>80
	SI	DCM (LED	sources)	3
	Be	eam angle	[°]	(C0-C180) / (C90-C270) - 82,4° / 76,2
		hotobiolog 2471)	ical risk class (IEC/EN	RG0
	Pr	rotection a	gainst electric shock	I
	Pr	rotection d	egree	IP40
	Vo	oltage		220240 V, 5060 Hz
	Li	Lifetime of LED sources [h]		100000
	L>	x/By		L80/B10
	0	perating te	emperature range [°C]	5 ÷ 35
	Di	river		standard on/off (E)
	Po	ower facto	r cos φ	>0,95
	Ci	ircuit load	capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)



Mechanical data	∏H ⊨→ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum anodised aluminum LOUVER (anti-glare louver) IK04 1120 x 60 x 70
A graph of light			105° 90° 75° 60° 45° 45° 480 45° 480 45° 60° 60° 60° 60° 45° 480 45° 480 45° 45° 480 45° 480 45° 480 45° 480 45° 45° 480 45° 45° 45° 45° 45° 45° 45° 45°




## Accessories


Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT




Index 19.2110.0003.24

Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 24





Index 19.2110.0004.24 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 24





Index 19.2110.0001.24

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.24 Name X-LINE PRO LOUVER LINE MIDDLE SET 24

