

## Product: X-LINE PRO 4000 LOUVER E 34 840 LINE / L-1120MM Index: 19.2110.3341.34



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


Product information	Cat	Category Surface mounted luminaires			
	Far	nily X-LINE	PRO LINE		
	Nar	ame X-LINE PRO 4000 LOUVER E 34 840 LINE / L-1120MM			
	Ind	ex <b>19.211</b> (	.3341.34		
Light and electrical data	Ligl	nt source		LED	
•		ninous flux LED [	lm]	4432	
	LED	power [W]		22,4	
	Lur	ninaire luminous	flux [lm]	4303,5	
	Pov	ver of luminaire [	W]	25,5	
	Lur	ninaire's light effi	ciency [lm/W]	168,8	
	Col	or of the light [K]		4000	
	CR			>80	
	SDO	CM (LED sources	6)	3	
	Bea	am angle [°]		(C0-C180) / (C90-C270) - 82,4° / 76,2	
	Pho 624	tobiological risk 71)	class (IEC/EN	RG0	
	Pro	tection against e	ectric shock	I	
	Pro	tection degree		IP40	
	Volt	age		220240 V, 5060 Hz	
	Life	Lifetime of LED sources [h]		100000	
	Lx/I	Зу		L80/B10	
	Ope	erating temperati	ure range [°C]	5 ÷ 35	
	Driv	ver		standard on/off (E)	
	Pov	ver factor $\cos \phi$		>0,95	
	Circ	cuit load capacity		25 (B10), 40 (B16), 39 (C10), 62 (C16)	



Mechanical data	∏tH ⊌++ B	Assembly Material	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum	
- A →	В	Color	RAL 9016 (white)	
		Diffuser	LOUVER (anti-glare louver)	
		Impact resistant	IK04	
		Dimensions [mm]	1120 x 60 x 70	
A graph of light			105° 90° 75° 60° 45° 45° 45° 480 45° 480 45° 45° 480 45° 45° 45° 45° 45° 45° 45° 45° 480 45° 45° 45° 45° 45° 45° 45° 45° 45° 45°	




## Accessories







Index 19.2110.0003.34

Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34












Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.34 Name X-LINE PRO LOUVER LINE MIDDLE SET 34



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025