

Product: X-LINE PRO 4000 LOUVER EDD 24 840 LINE / L-1120MM Index: 19.2110.3343.24



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	CategorySurface mounted luminFamilyX-LINE PRO LINENameX-LINE PRO 4000 LOUVIndex19.2110.3343.24	aires ER EDD 24 840 LINE / L-1120MM
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	4432
	LED power [W]	22,4
	Luminaire luminous flux [lm]	4303,5
	Power of luminaire [W]	25,5
	Luminaire's light efficiency [lm/W]	168,8
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor cos φ	>0,95
	Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)




Mechanical data	∏H ⊨→ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum anodised aluminum LOUVER (anti-glare louver) IK04 1120 x 60 x 70
A graph of light			105° 90° 75° 60° 45° 45° 480 45° 480 45° 60° 60° 60° 60° 45° 480 45° 480 45° 45° 480 45° 480 45° 480 45° 480 45° 45° 480 45° 45° 45° 45° 45° 45° 45° 45°




Accessories


Index 6E1-500KWAN1P-5 Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT




Index 19.2110.0003.24

Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 24





Index 19.2110.0004.24 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 24






Index 19.2110.0001.24

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.24 Name X-LINE PRO LOUVER LINE MIDDLE SET 24



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025