

Product: X-LINE PRO 4000 LOUVER EDD 34 840 LINE / L-1120MM

Index: 19.2110.3343.34



## **Description**

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

### **Product information**

Category	Surface mounted luminaires
Family	X-LINE PRO LINE
Name	X-LINE PRO 4000 LOUVER EDD 34 840 LINE / L-1120MM
Index	19.2110.3343.34
















## Light and electrical data

Light course	LED
Light source	
Luminous flux LED [lm]	4432
LED power [W]	22,4
Luminaire luminous flux [lm]	4303,5
Power of luminaire [W]	25,5
Luminaire's light efficiency [lm/W]	168,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)



Mechanical data	□──tн	Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Δ	<u> </u>	Material	aluminum
<u> </u>	D	Color	RAL 9016 (white)
		Diffuser	LOUVER (anti-glare louver)
		Impact resistant	IK04
		Dimensions [mm]	1120 x 60 x 70

# A graph of light









### **Accessories**


Index 6E1-500KW341P-5

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 19.2110.0003.34

Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34




Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 19.2110.0004.34

Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 34



Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE FRONT+END SET 34



Index 19.2110.0002.34

Name X-LINE PRO LOUVER LINE MIDDLE SET 34

