

Product: X-LINE PRO 6000 LOUVER E 04 840 LINE / L-1680MM Index: 19.2110.3441.04



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

| Product information | C | Category | Surface mounted luminai | res | |
|---------------------------|---|-----------------------------|---|---|--|
| | F | -amily | X-LINE PRO LINE | | |
| | 1 | Name | e X-LINE PRO 6000 LOUVER E 04 840 LINE / L-1680MM | | |
| | I | ndex | 19.2110.3441.04 | | |
| | | | | | |
| Light and electrical data | l | _ight source |) | LED | |
| | L | _uminous flu | ux LED [lm] | 6648 | |
| | L | _ED power | [W] | 33,6 | |
| | L | uminaire lu | ımin <mark>ous flux [lm]</mark> | 6455,2 | |
| | F | Power of lur | minaire [W] | 38,2 | |
| | L | _uminaire's | light efficiency [lm/W] | 169 | |
| | C | Color of the | light [K] | 4000 | |
| | C | CRI | | >80 | |
| | Ş | SDCM (LED | sources) | 3 | |
| | E | Beam angle | [°] | (C0-C180) / (C90-C270) - 82,4° / 76,2 | |
| | | Photobiolog 62471) | ical risk class (IEC/EN | RG0 | |
| | F | Protection a | gainst electric shock | I | |
| | F | Protection d | egree | IP40 | |
| | ١ | Voltage | | 220240 V, 5060 Hz | |
| | L | Lifetime of LED sources [h] | | 100000 | |
| | L | _x/By | | L80/B10 | |
| | (| Operating te | emperature range [°C] | 5 ÷ 35 | |
| | Γ | Driver | | standard on/off (E) | |
| | F | Power facto | r cos φ | >0,95 | |
| | (| Circuit load | capacity | 25 (B10), 40 (B16), 39 (C10), 62 (C16) | |



| Mechanical data | | Assembly | directly mounted to ceiling construction or surface mounted on slings using accessories | |
|------------------|--|------------------|---|--|
| | | Material | aluminum | |
| | | Color | RAL 9005 (black) | |
| | | Diffuser | LOUVER (anti-glare louver) | |
| | | Impact resistant | IK04 | |
| | | Dimensions [mm] | 1680 x 60 x 70 | |
| A graph of light | | | 105° 90° 75° 60° 45° 45° 45° 480 45° 480 45° 45° 45° 45° 45° 45° 45° 45° | |
| | | | | |
| | | | | |




Accessories









Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 04












Name X-LINE PRO LOUVER LINE FRONT+END SET 04







Index 19.2110.0002.04

