

Product: X-LINE PRO 6000 LOUVER EDD 04 840 LINE / L-1680MM Index: 19.2110.3443.04



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


Product information	Category Surface mounted luminaires			
	Family X-LINE PRO LINE	X-LINE PRO LINE		
	Name X-LINE PRO 6000 LOUVER EDD 04 840 LINE / L-1680MM	М		
	Index 19.2110.3443.04			
	Image: Second			
Light and electrical data	Light source LED			
	Luminous flux LED [lm] 6648			
	LED power [W] 33,6			
	Luminaire luminous flux [lm] 6455,2			
	Power of luminaire [W] 38,2			
	Luminaire's light efficiency [Im/W] 169			
	Color of the light [K] 4000			
	CRI >80			
	SDCM (LED sources) 3			
	Beam angle [°] (C0-C180) / (C90-C270) - 82,4	° / 76,2		
	Photobiological risk class (IEC/EN RG0 62471)			
	Protection against electric shock			
	Protection degree IP40			
	Voltage 220240 V, 5060 Hz			
	Lifetime of LED sources [h] 100000	100000		
	Lx/By L80/B10	L80/B10		
	Operating temperature range [°C] 5 ÷ 35	5 ÷ 35		
	Driver DIM DALI (EDD)	DIM DALI (EDD)		
	Power factor cos φ >0,95	>0,95		
	Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 4 (C16)	41		




Mechanical data	[]]н	Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
	l+++ B	Material	aluminum
		Color	RAL 9005 (black)
		Diffuser	LOUVER (anti-glare louver)
		Impact resistant	IK04
		Dimensions [mm]	1680 x 60 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 480 45° 480 45° 45° 45° 45° 45° 45° 45° 45°




Accessories









Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 04





Index 19.2110.0004.04 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 04






Index 19.2110.0001.04

Name X-LINE PRO LOUVER LINE



Index 19.2110.0002.04 Name X-LINE PRO LOUVER LINE MIDDLE SET 04



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025