

Product: X-LINE PRO 8000 LOUVER EDD 34 830 LINE / L-2240MM Index: 19.2110.3533.34



Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.


Product information	Category	Surface mounted luminaire	25
	Family 2	X-LINE PRO LINE	
		X-LINE PRO 8000 LOUVER	EDD 34 830 LINE / L-2240MM
	Index :	19.2110.3533.34	
Light and electrical data	Light source	9	LED
J.	Luminous flu	ux LED [lm]	8424
	LED power [[W]	44,8
	Luminaire luminous flux [lm]		8179,7
	Power of luminaire [W]		50,9
	Luminaire's light efficiency [lm/W]		160,7
	Color of the	light [K]	3000
	CRI		>80
	SDCM (LED	sources)	3
	Beam angle	[°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiological risk class (IEC/EN 62471)		RG0
	Protection against electric shock		I
	Protection degree		IP40
	Voltage		220240 V, 5060 Hz
	Lifetime of LED sources [h]		100000
	Lx/By		L80/B10
	Operating temperature range [°C]		5 ÷ 35
	Driver		DIM DALI (EDD)
	Power factor $\cos \phi$		>0,95
	Circuit load o	capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)




Mechanical data	∏tH ⊮+	Assembly Material	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum
l₄ A	D	Color	RAL 9016 (white)
		Diffuser	LOUVER (anti-glare louver)
		Impact resistant	IK04
		Dimensions [mm]	2240 x 60 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 320 45° 60° 45° 480 30° 15° 0° 15° 0° 15° 0° 15° 0° 15° 90° 90° 45° 480 45° 45° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15°




Accessories








Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 34







Index 19.2110.0004.34 Name X-LINE PRO LOUVER LINE SURFACE MIDDLE SET 34



Index 19.2110.0001.34

Name X-LINE PRO LOUVER LINE FRONT+END SET 34





Index 19.2110.0002.34 Name X-LINE PRO LOUVER LINE MIDDLE SET 34

