

## Product: X-LINE PRO 8000 LOUVER E 04 840 LINE / L-2240MM Index: 19.2110.3541.04



## Description

Light fitting made out of aluminium profile. Simple luminaire construction (no mounting plates or LED plates). LEDs in the standard version are mounted by inserting them into the slot in the middle of the profile. Direct (down) light distribution. Available optical systems: anti-glare louvre (silver, white or black on request). The luminaire is available in a line version. Available colors: anodized aluminum, black RAL 9005, white RAL 9016 or any color from the RAL palette on request. Gray, white or black polycarbonate end caps. Plastic plate (HIPS) masking the electronics compartment (only in luminaires with direct distribution). Possibility to use an aluminum snap-on aluminum cover. The use of luminaires typically for offices.

Product information	Category	Surface mounted luminair	es
	Family	X-LINE PRO LINE	
	Name	X-LINE PRO 8000 LOUVER	R E 04 840 LINE / L-2240MM
	Index	19.2110.3541.04	
Light and electrical data	Light source	ce	LED
	Luminous	flux LED [lm]	8864
	LED power	r [W]	44,8
	Luminaire	luminous flux [lm]	8606,9
	Power of lu	uminaire [W]	50,9
	Luminaire's light efficiency [lm/W]		169,1
	Color of the light [K]		4000
	CRI		>80
	SDCM (LED sources)		3
	Beam ang	e [°]	(C0-C180) / (C90-C270) - 82,4° / 76,2°
	Photobiological risk class (IEC/EN 62471)		RG0
	Protection against electric shock		I
	Protection degree		IP40
	Voltage		220240 V, 5060 Hz
	Lifetime of LED sources [h]		100000
	Lx/By		L80/B10
	Operating temperature range [°C]		5 ÷ 35
	Driver		standard on/off (E)
	Power factor $\cos \phi$		>0,95
	Circuit load	l capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	directly mounted to ceiling construction or surface mounted on slings using accessories aluminum RAL 9005 (black) LOUVER (anti-glare louver) IK04 2240 x 60 x 70
A graph of light			105° 105°   90° 90°   75° 90°   60° 320   45° 60°   45° 480   45° 480   45° 480   40° 15°   30° 15°   0° 15°   15° 9°




## **Accessories**









Name X-LINE PRO LOUVER LINE SURFACE FRONT+END SET 04












Name X-LINE PRO LOUVER LINE FRONT+END SET 04







Index 19.2110.0002.04

