

Product: EUROPANEL LED 5800 PLX E 34 IP65 840 Index: 19.3054.0082.34



Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminary body made from aluminum. PMMA opal diffuser. Colour of luminary - white. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc. The level of protection against solid substances, dust and moisture penetration is IP65.

Product in	nformation
------------	------------

Category	Recessed luminaires	
Family	EUROPANEL LED IP65	
Name	EUROPANEL LED 5800 PLX E 34 IP65 840	
Index	19.3054.0082.34	
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \end{tabular}} \fbox{\begin{tabular}{ c c c c } \hline \end{tabular}} \vcenter{\begin{tabular}{ c c c c } \hline \end{tabular}} \fbox{\begin{tabular}{ c c c c c } \hline \end{tabular}} \vcenter{\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$	

Light and electrical data

Light source	LED
Luminous flux LED [lm]	6198
LED power [W]	34
Luminaire luminous flux [lm]	4487
Power of luminaire [W]	45,6
Luminaire's light efficiency [lm/W]	98,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 115,4° / 107,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 80000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 35 (B16), 37 (C10), 59 (C16)
	LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] CRI SDCM (LED sources) Beam angle [°] Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] Driver Power factor cos φ



60°

45

30° η = 72%


Mechanical data Assembly mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted (using accessories) Material aluminum B Color RAL 9016 (white) Diffuser PLX (PMMA opal) Ťн IK04 Impact resistant Weight [kg] 5,6 Dimensions [mm] 596 x 596 x 36 A graph of light 105 105 90 75°

Accessories

- Index 2C1A7392-34R
- Name EUROPANEL / BACKPANEL / RIM COMPACT LED RECESSED ACCESSORIES 34 / 600X600




Index 19.3213.0073.34 Name BACKPANEL LED SURFACE ACCESSORIES 34 / 600X600



Index 19.3213.0082.34

Name BACKPANEL LED SURFACE ACCESSORIES COMPACT 34 / 600X600

cd/klm _____ C0 - C180



Index 19.3213.0083.34

100

150

200

300

00

159

- C90 - C270

Name BACKPANEL LED SURFACE ACCESSORIES BASIC 34 / 600X600x70

15

