

Product: RING T 460 LED 6800 PLX L-DOWN E 34 IP43 840

Index: 19.3057.0003.34



Description

Sophisticated luminary providing the effect of a lighting ring designed for plasterboard ceilings, equipped with highly efficient LED sources. The luminary provides possibility for unique illumination of interior. The color rendering indicator is Ra>80. Luminary body is made from powder coated steel sheet in white. The luminary diffuser is made from opal PMMA. Luminary is protected against water and dust penetration – IP43. It has the first class protection against the electric shock. It is possible to mount the luminary in modular ceilings, provided that the luminaire is suspended from the main ceiling. Security (links etc.) on the client side

Product information

Category	Recessed luminaires
Family	RING T LED
Name	RING T 460 LED 6800 PLX L-DOWN E 34 IP43 840
Index	19.3057.0003.34
EAN	5902107066802















Light and electrical data

LED
6808
50
3076
56
54,9
4000
>80
(C0-C180) / (C90-C270) - 125,2° / 125,2°
I
IP43
220240 V, 5060 Hz
36000
L70/B50
5 ÷ 30
standard on/off (E)
>0.95
,

Mechanical data



T_H

Assembly	mounted in plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	3,8
Dimensions [mm]	Ø475 x 70
Mounting hole [mm]	Ø465



A graph of light





