

Product: TEAR LED 3000 NARROW E 34 SURFACE BASE 830

Index: 19.3069.0013.34



Description

The TEAR LED luminary is highly recommended for lighting the shop windows, shops' interiors, commercial spaces, the centers of culture and art – everywhere where the lighting emphasis is put on the singular items and attracts the customers attention. The luminary is used for the highly efficient LED panels of the leading lighting companies. TEAR LED is adapted to be mounted on a three-phase track, or on ceiling by a ceiling base. The body is made from the aluminum cast. Colour: white or black.

Product information

Category	Projectors
Family	TEAR LED SURFACE BASE
Name	TEAR LED 3000 NARROW E 34 SURFACE BASE 830
Index	19.3069.0013.34
EAN	5901867470195



Light and electrical data

Light source	LED
Luminous flux LED [lm]	3660
LED power [W]	24
Luminaire luminous flux [lm]	3031
Power of luminaire [W]	28
Luminaire's light efficiency [lm/W]	108,3
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 32,6° / 32,6°
Photobiological risk class (IEC/EN 62471)	RG1
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	84000
Lx/By	L90/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	39 (B10), 62 (B16), 65 (C10), 104 (C16)

Mechanical data



Assembly	mounted on ceiling by a ceiling base
Material	aluminum
Color	RAL 9016 (white)
Diffuser	transparent glass
Impact resistant	IK04
Weight [kg]	1,88
Dimensions [mm]	Ø130 x 275

A graph of light

