

Product: TEAR LED 5000 NARROW E 34 SURFACE BASE 840

Index: 19.3069.0022.34



Description

The TEAR LED luminaire is highly recommended for lighting the shop windows, shops' interiors, commercial spaces, the centers of culture and art – everywhere where the lighting emphasis is put on the singular items and attracts the customers attention. The luminaire is used for the highly efficient LED panels of the leading lighting companies. TEAR LED is adapted to be mounted on a three-phase track, or on ceiling by a ceiling base. The body is made from the aluminum cast. Colour: white or black.

Product information

Category	Projectors
Family	TEAR LED SURFACE BASE
Name	TEAR LED 5000 NARROW E 34 SURFACE BASE 840
Index	19.3069.0022.34
EAN	5901867470157



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5916
LED power [W]	37
Luminaire luminous flux [lm]	4899
Power of luminaire [W]	41
Luminaire's light efficiency [lm/W]	119,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 32,6° / 32,6°
Photobiological risk class (IEC/EN 62471)	RG1
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	83000
Lx/By	L90/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 35 (B16), 37 (C10), 59 (C16)

Mechanical data



Assembly	mounted on ceiling by a ceiling base
Material	aluminum
Color	RAL 9016 (white)
Diffuser	transparent glass
Impact resistant	IK04
Weight [kg]	1,75
Dimensions [mm]	Ø130 x 275

A graph of light

