

Product: ONLINE LED 2600 PLX E 24 840 LINE-EP / L-567MM

Index: 19.3091.0005.24



Description

Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

Product information

Category	Surface mounted luminaires
Family	ONLINE LED LINE
Name	ONLINE LED 2600 PLX E 24 840 LINE-EP / L-567MM
Index	19.3091.0005.24
















Light and electrical data

LED
2617
13,3
2065
14,4
143,4
4000
>80
3
(C0-C180) / (C90-C270) - 93,8° / 96,6°
I
IP20
220240 V, 5060 Hz
100000 (1) / 147000 (2)
L80/B10 (1) / L70/B50 (2)
5 ÷ 30
standard on/off (E)
>0,95
22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data






Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	567 x 92 x 86



A graph of light



Accessories

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT




Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT

