

Product: ONLINE LED 4400 PLX E 34 840 LINE-EP / L-567MM Index: 19.3091.0014.34



Description


Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

| Product information | Category | Category Surface mounted luminaires | |
|---------------------------|--------------|-------------------------------------|---|
| | Family | ONLINE LED LINE | |
| | Name | ONLINE LED 4400 | PLX E 34 840 LINE-EP / L-567MM |
| | Index | 1 <mark>9.3091</mark> .0014.34 | |
| | | | |
| Light and electrical data | Light source | ce | LED |
| 5 | Luminous | flux LED [lm] | 4565 |
| | LED power | r [W] | 23,4 |
| | Luminaire | luminous flux [lm] | 3602 |
| | Power of Iu | uminaire [W] | 24,7 |
| | | s light efficiency [lm/W] | 145,8 |
| | Color of the | e light [K] | 4000 |
| | CRI | | >80 |
| | SDCM (LE | D sources) | 3 |
| | Beam angl | le [°] | (C0-C180) / (C90-C270) - 93,8° / 96,6° |
| | Protection | against electric shock | I |
| | Protection | degree | IP20 |
| | Voltage | | 220240 V, 5060 Hz |
| | Lifetime of | LED sources [h] | 100000 (1) / 147000 (2) |
| | Lx/By | | L80/B10 (1) / L70/B50 (2) |
| | | temperature range [°C | c] 5 ÷ 30 |
| | Driver | | standard on/off (E) |
| | Power fact | or cos φ | >0,95 |
| | Circuit load | 1 capacity | 30 (B10), 48 (B16), 43 (C10), 70 (C16) |
| Mechanical data | Assembly | | ectly mounted to ceiling construction or rface mounted on slings |
| | Material | alu | iminum |
| | Color | RA | L 9016 (white) |
| | Diffuser | PL | X (PMMA opal) |
| | Impact res | istant IKO |)4 |
| | | | |

Dimensions [mm]

567 x 92 x 86

A graph of light



Accessories

Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT




Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025