

Product: ONLINE LED 5200 PLX E 34 840 LINE-S / L-1200

Index: 19.3091.0021.34



Description

Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

Product information

| Category | Surface mounted luminaires |
|----------|--|
| Family | ONLINE LED LINE |
| Name | ONLINE LED 5200 PLX E 34 840 LINE-S / L-1200 |
| Index | 19.3091.0021.34 |
















Light and electrical data

| LED |
|--|
| 5234 |
| 26,6 |
| 4130 |
| 28,2 |
| 146,5 |
| 4000 |
| >80 |
| 3 |
| (C0-C180) / (C90-C270) - 93,8° / 96,6° |
| 1 |
| IP20 |
| 220240 V, 5060 Hz |
| 100000 (1) / 147000 (2) |
| L80/B10 (1) / L70/B50 (2) |
| 5 ÷ 30 |
| standard on/off (E) |
| >0,95 |
| 30 (B10), 48 (B16), 43 (C10), 70 (C16) |
| |

Mechanical data






| Assembly | directly mounted to ceiling construction or surface mounted on slings |
|------------------|--|
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Dimensions [mm] | 1124 x 92 x 86 |



A graph of light



Accessories

Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT

