

Product: ONLINE LED 17600 PLX E 34 840 LINE-S / L-2400

Index: 19.3091.0055.34



Description

Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

Product information

Category	Surface mounted luminaires
Family	ONLINE LED LINE
Name	ONLINE LED 17600 PLX E 34 840 LINE-S / L-2400
Index	19.3091.0055.34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	18261
LED power [W]	93,6
Luminaire luminous flux [lm]	14408
Power of luminaire [W]	100,5
Luminaire's light efficiency [lm/W]	143,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 93,8° / 96,6°
Protection against electric shock	I
Protection degree	IP20
Voltage	
voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	220240 V, 5060 Hz 100000 (1) / 147000 (2)
	, , , , , , , , , , , , , , , , , , ,
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lifetime of LED sources [h] Lx/By	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30

Mechanical data






Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	2244 x 92 x 86



A graph of light



Accessories

Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT

