

Product: KUBIK WALL ECO LED UP&DOWN 1X G9 IP20 34

Index: 19.3019.1001.34



Description

Luminaire for interchangeable LED sources (called retrofit) with a G9 base. The body is made of aluminum. The open design provides very easy access to the source and its replacement, and very easy mounting on the wall as well. Simple construction giving an interesting light effect. Recommended for decorative lighting of passages, corridors or staircases.

Product information


| | |
|----------|--|
| Category | Architectural luminaires |
| Family | KUBIK WALL ECO LED IP20 |
| Name | KUBIK WALL ECO LED UP&DOWN 1X G9 IP20 34 |
| Index | 19.3019.1001.34 |
| EAN | 5902107135164 |



Light and electrical data

| | |
|-------------------------------------|--|
| Light source | RETROFIT G9 (not included) |
| Luminous flux LED [lm] | depending on source |
| LED power [W] | depending on source |
| Luminaire luminous flux [lm] | depending on source |
| Power of luminaire [W] | depending on source |
| Luminaire's light efficiency [lm/W] | depending on source |
| Color of the light [K] | depending on source |
| CRI | depending on source |
| SDCM (LED sources) | depending on source |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109° / 107,2° |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | depending on source |
| Lx/By | depending on source |
| Driver | none |

Mechanical data



| | |
|-----------------|------------------|
| Assembly | mounted on wall |
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | none |
| Weight [kg] | 0,63 |
| Dimensions [mm] | 120 x 120 x 120 |

A graph of light

