

**Product:** KUBIK 1D 1800 SYM E IP65 840 25 / L-900

**Index:** 19.3146.0007.25



## Description

Outdoor luminaire to be mounted on dedicated. The product is equipped with the newest generation of highly efficient LED light sources. LED module is additionally sealed with a special lens which at the same time ensures optimal wide light distribution. The housing is resistant to corrosion and is made of aluminum lacquered with facade paint. The product is dedicated for decorative illumination of walking paths, parks, recreational areas, residential areas, gardens and allotment gardens. The level of protection against solid substances, dust and moisture penetration is: IP65.

## Product information


Category	Outdoor luminaires
Family	KUBIK 1D LED
Name	KUBIK 1D 1800 SYM E IP65 840 25 / L-900
Index	19.3146.0007.25



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	1800
LED power [W]	13
Luminaire luminous flux [lm]	804
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	57,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	asymmetric light distribution
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-25 ÷ 50
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 25 (C10), 40 (C16)

## Mechanical data



Assembly	for the ground
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	none
Impact resistant	IK03
Weight [kg]	2,3
Dimensions [mm]	152 x 120 x 900

## A graph of light



## Accessories

Index 20ROFUB0.311000

Name B-0 Foundations

