

**Product:** KUBIK CEILING ECO LED 2X GU10 IP54 25

**Index:** 19.3148.0002.25



## Description

Architectural luminaire designed for ceiling mounting. The body is made of aluminum. Interchangeable light sources with the popular GU10 socket. The ergonomic shapes of the luminaire allow the use of KUBIK in almost every building. Very easy assembly. Luminaire with IP54 protection rating.

## Product information


Category	Outdoor luminaires
Family	KUBIK CEILING ECO LED
Name	KUBIK CEILING ECO LED 2X GU10 IP54 25
Index	19.3148.0002.25



## Light and electrical data

Light source	RETROFIT GU10 (not included)
Luminous flux LED [lm]	depending on applied light source
LED power [W]	depending on applied light source
Luminaire luminous flux [lm]	depending on applied light source
Power of luminaire [W]	depending on applied light source
Luminaire's light efficiency [lm/W]	depending on applied light source
Color of the light [K]	depending on applied light source
CRI	depending on applied light source
SDCM (LED sources)	depending on applied light source
Beam angle [°]	(C0-C180) / (C90-C270) - 111,4° / 111,4°
Protection against electric shock	I
Protection degree	IP54
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	depending on applied light source
Lx/By	depending on applied light source
Driver	none

## Mechanical data



Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK04
Weight [kg]	1,2
Dimensions [mm]	200 x 120 x 120

## A graph of light

