

Product: KUBIK CEILING SHORT LED 2X2,4W PC 3000K E IP65 25

Index: 19.3150.0003.25



Description

An outdoor fitting designed for ceiling mounting. The body is made of aluminum. Energy-efficient fitting made of component parts produced by renowned companies. Ergonomic shapes of the fitting enable the application of the Kubik-type fitting almost in every building. The assembly is very easy. Level of protection against penetration of dust and water - IP65.

Product information

Category	Outdoor luminaires
Family	KUBIK CEILING SHORT LED
Name	KUBIK CEILING SHORT LED 2X2,4W PC 3000K E IP65 25
Index	19.3150.0003.25



Light and electrical data

Light source	LED
Luminous flux LED [lm]	310
LED power [W]	5
Luminaire luminous flux [lm]	132
Power of luminaire [W]	7
Luminaire's light efficiency [lm/W]	18,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	5
Beam angle [°]	(C0-C180) / (C90-C270) - 111,4° / 111,4°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,5
Circuit load capacity	80 (B10), 157 (B16), 265 (C10), 317 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK04
Weight [kg]	0,5
Dimensions [mm]	100 x 100 x 120

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 02-07-2022