


**Product:** KUBIK SLIM LED 1X2,4W 5°-21°/4000K E IP65 34

**Index:** 19.3154.0004.34



## Description

An outdoor fitting made for illuminating building facades and creating lighting effects. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. It is possible to use various LED colours at the request of a customer. Ergonomic shapes of the fitting enable the application of the Kubik-type fitting almost in every building. The assembly and accessibility of the internal parts are very easy. The fitting is featured by a high level of protection against the penetration of solids and water: IP65, which renders the fitting an interesting decorative solution highlighting the architecture of an illuminated building. Kubik LED Slim luminaire relative to the standard version has a smaller height. Kubik LED Slim is more slim, and thus stands out from the wall for only 5 cm.

## Product information

Category	<b>Outdoor luminaires</b>
Family	<b>KUBIK SLIM LED</b>
Name	<b>KUBIK SLIM LED 1X2,4W 5°-21°/4000K E IP65 34</b>
Index	<b>19.3154.0004.34</b>
EAN	<b>5902107180560</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>187</b>
LED power [W]	<b>2</b>
Luminaire luminous flux [lm]	<b>155</b>
Power of luminaire [W]	<b>4</b>
Luminaire's light efficiency [lm/W]	<b>38,8</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 9,6° / 37°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP65</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>50000</b>
Lx/By	<b>L70/B50</b>
Operating temperature range [°C]	<b>-25 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,5</b>
Circuit load capacity	<b>80 (B10), 157 (B16), 265 (C10), 317 (C16)</b>

**Mechanical data**



Assembly	<b>mounted on wall</b>
Material	<b>aluminum</b>
Color	<b>RAL 9016 (white)</b>
Diffuser	<b>transparent polycarbonate</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>100 x 54 x 100</b>

**A graph of light**

