

Product: KUBIK POLE 4D 2000 FLOOD E IP65 840 / L-1100 RAL7021

Index: 19.3158.0001.00



## **Description**

Openwork construction with big notches of side planes which creates impression of lightness. Hermetic LED module with an integrated lens which ensures fourway, symetrical light distribution. Mounting in the substrate on the specially designed foundations. Available to the customer request an option with luminous flux reduction or dimmable DALI. Application: illumination of walking paths, parks, recreational areas, residential areas, gardens, allotment gardens. The level of protection against penetration of solid substances, dust and moisture is: IP65.

#### **Product information**

Category	Outdoor luminaires
Family	KUBIK POLE 4D
Name	KUBIK POLE 4D 2000 FLOOD E IP65 840 / L-1100 RAL7021
Index	19.3158.0001.00
ΕΔNI	5002107147525













#### Light and electrical data

Light source	LED
Luminous flux LED [lm]	3108
LED power [W]	16,2
Luminaire luminous flux [lm]	2411
Power of luminaire [W]	18,4
Luminaire's light efficiency [lm/W]	131
Color of the light [K]	4000
CRI	>80
Beam angle [°]	asymmetric light distribution
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	91000 (1) / 100000 (2) / 100000 (3)
Lx/By	L90/B10 (1) / L80/B10 (2) / L70/B10 (3)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	11 (B10), 17 (B16), 18 (C10), 29 (C16)


#### Mechanical data



Assembly	for the ground
Material	aluminum
Color	RAL 7021 (grey black)
Diffuser	none
Impact resistant	IK08
Weight [kg]	6,4
Dimensions [mm]	220 x 220 x 1100



# A graph of light



### **Accessories**

Index 2TJ5782-3

Name 5782-3 Foundations RAL9007



Index 2TJ5782-4

Name 5782-4 Foundations

