


**Product: KUBIK POLE 900 2/2/2/2 LED 1,7W E IP65 22 3000K** 

Index: 19.3160.0077.22



## **Description**

Outdoor luminary for assembling on a hardened surface (concrete, sett, or basement) equipped with the highly effective power saving LED sources of the newest generation. It is dedicated to illuminate pedestrian router such as park alleys, parking spaces communication routes, estate entrances. Luminary body coated with facade paint dedicated for outdoor usage, light sources placed in upper part of the luminary with the asymmetric lens providing illumination of the area. IP65 hermetic luminary, IK09 strike resistant. Luminary available in variety of colors from RAL color palette upon the clients request. Luminary height: 300, 600, 900, 3000 and 4000 mm.

#### **Product information**

Category	Outdoor luminaires
Family	KUBIK POLE LED
Name	KUBIK POLE 900 2/2/2/2 LED 1,7W E IP65 22 3000K
Index	19.3160.0077.22
EAN	5901867439116














### Light and electrical data

Light source	LED
Luminous flux LED [lm]	992
LED power [W]	14
Luminaire luminous flux [lm]	807
Power of luminaire [W]	15
Luminaire's light efficiency [lm/W]	53,8
Color of the light [K]	3000
CRI	>80
Beam angle [°]	asymmetric light distribution
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,5


### Mechanical data



Assembly	for the ground
Material	aluminum
Color	RAL 9007 (dark grey, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK09
Weight [kg]	7,46
Dimensions [mm]	150 x 150 x 900



# A graph of light



### **Accessories**

Index 2TJ5782-3

Name 5782-3 Foundations RAL9007



Index 2TJ5782-4

Name 5782-4 Foundations

