

Product: KUBIK POLE 600 2/2/2/2 LED 1,7W ODB E IP65 22 3000K

Index: 19.3161.0047.22



## **Description**

Outer luminary to be mounted on a solid surface (concrete, sett, or substructure) equipped with highly efficient energy saving LED sources of the newest generation. Luminary dedicated to illuminate pedestrians routes such as park alleys, parking site passages, property entrances. Its body made from aluminum which is coated by the facade powder used for outdoor activities. LED sources are placed in the upper part of the luminary, and hidden within the construction, invisible for a potential viewer. Optical system used in the product provides asymmetric light distribution. Luminary is hermetic (IP65) – it guarantees no dust or water penetration. It is also shockproof (IK09). Luminary available in different colors from RAL palette upon the customer's request. Luminary height: 300, 600, 900, 3000 and 4000 mm.

#### **Product information**

Category	Outdoor luminaires
Family	KUBIK POLE LED ODB
Name	KUBIK POLE 600 2/2/2/2 LED 1,7W ODB E IP65 22 3000K
Index	19.3161.0047.22
EAN	5901867477910














## Light and electrical data

Light source	LED
Luminous flux LED [lm]	992
LED power [W]	14
Luminaire luminous flux [lm]	828
Power of luminaire [W]	15
Luminaire's light efficiency [lm/W]	55,2
Color of the light [K]	3000
CRI	>80
Beam angle [°]	asymmetric light distribution
Protection against electric shock	I
Protection degree	IP65
Voltago	
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	220240 V, 5060 Hz 50000
	,
Lifetime of LED sources [h]	50000
Lifetime of LED sources [h] Lx/By	50000 L70/B50
Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	50000 L70/B50 -25 ÷ 30


#### Mechanical data



Assembly	for the ground
Material	aluminum
Color	RAL 9007 (dark grey, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK09
Weight [kg]	5,6
Dimensions [mm]	150 x 150 x 600



# A graph of light



## **Accessories**

Index 2TJ5782-3

Name 5782-3 Foundations RAL9007



Index 2TJ5782-4

Name 5782-4 Foundations

