

Product: KUBIK POLE 900 4/2/4/2 LED 1,7W ODB E IP65 22 3000K Index: 19.3161.0089.22



Description

Outer luminary to be mounted on a solid surface (concrete, sett, or substructure) equipped with highly efficient energy saving LED sources of the newest generation. Luminary dedicated to illuminate pedestrians routes such as park alleys, parking site passages, property entrances. Its body made from aluminum which is coated by the facade powder used for outdoor activities. LED sources are placed in the upper part of the luminary, and hidden within the construction, invisible for a potential viewer. Optical system used in the product provides asymmetric light distribution. Luminary is hermetic (IP65) – it guarantees no dust or water penetration. It is also shockproof (IK09). Luminary available in different colors from RAL palette upon the customer's request. Luminary height: 300, 600, 900, 3000 and 4000 mm.


Product information	Category Outdoor lumin	aires
	Family KUBIK POLE L	ED ODB
		00 4/2/4/2 LED 1,7W ODB E IP65 22 3000K
	Index 19.3161.0089.2	
	EAN 590186747833	7
Light and electrical data	Light source	LED
	Luminous flux LED [Im]	1488
	LED power [W]	20
	Luminaire luminous flux [Im] 1243
	Power of luminaire [W]	23
	Luminaire's light efficiency [[m/W] 54
	Color of the light [K]	3000
	CRI	>80
	Beam angle [°]	asymmetric light distribution
	Protection against electric s	hock I
	Protection degree	IP65
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	50000
	Lx/By	L70/B50
	Operating temperature rang	ge [°C] -25 ÷ 30
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,5
	Circuit load capacity	20 (B10), 30 (B16), 33 (C10), 53 (C16)
Mechanical data	Assembly	for the ground
	Material	aluminum
	Color	RAL 9007 (dark grey, metallic, fine structure)
	Diffuser	transparent polycarbonate
	Impact resistant	IK09
	Weight [kg]	7,4
	0 1 0,	•

Dimensions [mm]

150 x 150 x 900



A graph of light



Accessories

Index 2TJ5782-3 Name 5782-3 Foundations RAL9007



Index 2TJ5782-4 Name 5782-4 Foundations

