

Product: KUBIK POLE T 10000 STREET-M E IP65 04 757 / 4000/1700MM Index: 19.3164.0002.04




Description

Outdoor luminary for assembling on a hardened surface (concrete, sett, or basement) equipped with the highly effective power saving LED sources of the newest generation. The system is designed and optimized for lighting streets, parks, gardens. Corrosion resistant extruded aluminum aesthetic housing and special pole arrangement. Easy installation, tool less, easy maintenance. Optimal performance with a glare-free, full cutoff, uniform lighting distribution. Note: Luminaires up to 6 m high can be safely used in the first and third wind zones (according to PN-EN 1991-1-4) and in the third and fourth terrain categories (according to PN-EN 40-3-1: 2004). Il wind zone and other terrain categories require an individual assessment of the maximum binding height. The type and dimensions of the foundation each time depend on the foundation conditions. The final selection of the foundation, in accordance with the Building Law, is the responsibility of the designer of the object.

| Product information | Category Outdoor luminaires |
|---------------------------|--|
| | Family KUBIK POLE T LED |
| | Name KUBIK POLE T 10000 STREET-M E IP65 04 757 / 4000/1700MM |
| | Index 19.3164.0002.04 |
| | EAN 5902107188986 |
| | |
| Light and electrical data | Light source LED |
| | Luminous flux LED [Im] 9933 |
| | LED power [W] 67 |
| | Luminaire luminous flux [Im] 9400 |
| | Power of luminaire [W] 75 |
| | Luminaire's light efficiency [lm/W] 125,3 |
| | Color of the light [K] 5700 |
| | CRI >70 |
| | Beam angle [°] street light distribution |
| | Protection against electric shock |
| | Protection degree IP65 |
| | Voltage 220240 V, 5060 Hz |
| | Lifetime of LED sources [h] 50000 |
| | Lx/By L70/B10 |
| | Operating temperature range [°C] -25 ÷ 30 |
| | Driver standard on/off (E) |
| | Power factor cos φ >0,95 |
| | Circuit load capacity 6 (B10), 10 (B16), 10 (C10), 17 (C16) |
| Mechanical data | Assembly for the ground |
| | Material aluminum |
| | Color RAL 9005 (black) |
| | Diffuser transparent polycarbonate |
| | Impact resistant IK04 |
| | Dimensions [mm] 1700 x 260 x 4000 |
| ۵۵ ۸ | |

A graph of light



Accessories

Index 17ROFU311151 Name B-51 Foundations



Index 50RO4008 Name ROSA set of galvanized nuts for B-60



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025