

Product: KUBIK WALL ECO LED UP OR DOWN 1X G9 IP54 25

Index: 19.3165.0001.25



Description

Luminaire for removable LED sources, called Retofit, matching the G9 holder. The body is made of aluminum painted with a special facade paint resistant to weather conditions. PMMA opal. Very easy assembly and access to the interior. Recommended for balconies lighting.

Product information

Category	Outdoor luminaires	
Family	KUBIK WALL ECO LED IP54	
Name	KUBIK WALL ECO LED UP OR DOWN 1X G9 IP54 25	
Index	19.3165.0001.25	
FAN	5902107151850	










Light and electrical data

Light source	RETROFIT G9 (not included)
Luminous flux LED [lm]	depending on source
LED power [W]	depending on source
Luminaire luminous flux [lm]	depending on source
Power of luminaire [W]	depending on source
Luminaire's light efficiency [lm/W]	depending on source
Color of the light [K]	depending on source
CRI	depending on source
SDCM (LED sources)	depending on source
Beam angle [°]	(C0-C180) / (C90-C270) - 111,4° / 111,4°
Protection against electric shock	I
Protection degree	IP54
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	depending on source
Lx/By	depending on source
Driver	none

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PMMA opal
Weight [kg]	0,89
Dimensions [mm]	100 x 100 x 110



A graph of light

