

Product: KUBIK WALL SHORT LED UP OR DOWN 2X2,4W PC 4000K E IP65 04

Index: 19.3167.0004.04



Description

A luminaire made for illuminating building facades. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. Ergonomic shapes of the fitting enable the application almost in every building. The assembly is very easy. The fitting is featured by a high level of protection against the penetration of solids and water IP65.

Product information

Category	Outdoor luminaires
Family	KUBIK WALL SHORT LED UP OR DOWN
Name	KUBIK WALL SHORT LED UP OR DOWN 2X2,4W PC 4000K E IP65 04
Index	19.3167.0004.04
EAN	5902107142780














Light and electrical data

1 = 5
LED
374
5
160
7
22,9
4000
>80
(C0-C180) / (C90-C270) - 111,4° / 111,4°
I
IP65
•
IP65
IP65 220240 V, 5060 Hz
IP65 220240 V, 5060 Hz 50000
IP65 220240 V, 5060 Hz 50000 L70/B50
IP65 220240 V, 5060 Hz 50000 L70/B50 -25 ÷ 30

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK08
Weight [kg]	0,5
Dimensions [mm]	100 x 100 x 130



A graph of light

