

Product: KUBIK WALL SHORT LED UP OR DOWN 2X1,7W PC 3000K E IP65 25

Index: 19.3167.0001.25



Description

A luminaire made for illuminating building facades. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. Ergonomic shapes of the fitting enable the application almost in every building. The assembly is very easy. The fitting is featured by a high level of protection against the penetration of solids and water IP65.

Product information

| Category | Outdoor luminaires | |
|----------|---|--|
| Family | KUBIK WALL SHORT LED UP OR DOWN | |
| Name | KUBIK WALL SHORT LED UP OR DOWN 2X1,7W PC 3000K E IP65 25 | |
| Index | 19.3167.0001.25 | |
| EAN | 5902107258825 | |
















Light and electrical data

| Light source | LED |
|-------------------------------------|--|
| Luminous flux LED [lm] | 248 |
| LED power [W] | 3 |
| Luminaire luminous flux [lm] | 106 |
| Power of luminaire [W] | 5 |
| Luminaire's light efficiency [lm/W] | 21,2 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 111,4° / 111,4° |
| Protection against electric shock | 1 |
| Protection degree | IP65 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 50000 |
| Lx/By | L70/B50 |
| Operating temperature range [°C] | -25 ÷ 30 |
| Driver | standard on/off (E) |
| Driver | (_, |
| Power factor cos φ | >0,5 |

Mechanical data



| Assembly | mounted on wall |
|------------------|---|
| Material | aluminum |
| Color | RAL 7016 (anthracite, metallic, fine structure) |
| Diffuser | PC (opalescent polycarbonate) |
| Impact resistant | IK08 |
| Weight [kg] | 0,5 |
| Dimensions [mm] | 100 x 100 x 130 |



A graph of light

