

Product: KUBIK WALL SHORT LED UP OR DOWN 2X1,7W PC 3000K E IP65 34

Index: 19.3167.0001.34



Description

A luminaire made for illuminating building facades. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. Ergonomic shapes of the fitting enable the application almost in every building. The assembly is very easy. The fitting is featured by a high level of protection against the penetration of solids and water IP65.

Product information

Category	Outdoor luminaires
Family	KUBIK WALL SHORT LED UP OR DOWN
Name	KUBIK WALL SHORT LED UP OR DOWN 2X1,7W PC 3000K E IP65 34
Index	19.3167.0001.34
EAN	5902107258771



Light and electrical data

Light source	LED
Luminous flux LED [lm]	248
LED power [W]	3
Luminaire luminous flux [lm]	106
Power of luminaire [W]	5
Luminaire's light efficiency [lm/W]	21,2
Color of the light [K]	3000
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 111,4° / 111,4°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,5
Circuit load capacity	80 (B10), 157 (B16), 265 (C10), 317 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK08
Weight [kg]	0,5
Dimensions [mm]	100 x 100 x 130

A graph of light

