

Product: KUBIK LED 1X7,2W 5°-21°/6500K E IP65 21 / 150X150

Index: 19.3169.0003.21



## **Description**

An outdoor fitting made for illuminating building facades and creating lighting effects. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. It is possible to use various LED colours at the request of a customer. Ergonomic shapes of the fitting enable the application of the Kubik-type fitting almost in every building. The assembly and accessibility of the internal parts are very easy. The fitting is featured by a high level of protection against the penetration of solids and water: IP65, which renders the fitting an interesting decorative solution highlighting the architecture of an illuminated building.

### **Product information**

Category	Outdoor luminaires	
Family	KUBIK LED	
Name	KUBIK LED 1X7,2W 5°-21°/6500K E IP65 21 / 150X150	
Index	19.3169.0003.21	
EAN	5902107140250	














## Light and electrical data

Light source	LED
Luminous flux LED [lm]	639
LED power [W]	7
Luminaire luminous flux [lm]	531
Power of luminaire [W]	9
Luminaire's light efficiency [lm/W]	59
Color of the light [K]	6500
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 9,6° / 37°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,5
Circuit load capacity	80 (B10), 157 (B16), 265 (C10), 317 (C16)

### Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9006 (grey, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK09
Weight [kg]	0,48
Dimensions [mm]	150 x 150 x 135



# A graph of light

